

## UPV - kovové rozvodnice pod omietku

f-tronic®



UPV

UPV

UPV

- Určené pre **montáž pod omietku**,
- **dobávané s PE a N svorkovnicami**,
- veľký priestor za DIN lištou pre vedenie vodičov,
- **12 + 2 modulov v jednom rade**,
- pre prístroje do 63 A,
- hrúbka rámu len 9 mm.



UPV 12+2 ST

UPV 24+4 ST

UPV 36+6 ST

UPV 48+8 ST

UPV 60+10 ST

Typ	Počet modulov	Počet radov	Počet modulov v rade	Svorkovnica	Rozmer V × Š × H [mm]
UPV 12+2 ST	14	1	14	PE + N	400 × 365 × 98
UPV 24+4 ST	28	2	14	PE + N	525 × 365 × 98
UPV 36+6 ST	42	3	14	PE + N	650 × 365 × 98
UPV 48+8 ST	56	4	14	PE + N	775 × 365 × 98
UPV 60+10 ST	70	5	14	PE + N	900 × 365 × 98

### Technické parametre

Materiál	dvierka: ocel / zvyšné časti: PS-HI
Rozmerová a tvarová stálosť	max. 70 °C
Test žeravým drôtom	850 °C
Krytie	IP 30

### Príslušenstvo:



klúč TSV  
(strana 47)

mostík N286-1  
(strana 47)

mostík PEN286-1  
(strana 47)

mostík SKH17N  
(strana 47)

mostík SKH17PE  
(strana 47)